

Appendix C, Pricing Index
Champion Optical Network Engineering LLC dba Champion ONE
DIR-CPO-4418

PRODUCT DESCRIPTION	DIR Customer Discount % off MSRP
Passport - Universal: 550m Short Haul SFP	85.07%
Passport - Universal: 550m Short Haul SFP, Temperature Hardened	63.58%
Sureport- Cisco: SFP 1000Base-SX 550m, Cisco Systems compatible, OEM PN: GLC-SX-MM GLC-SX-MMD SFP-GE-S (GLC-SX-MM-RGD)	81.49%
Sureport- HP: SFP 1000Base-SX 550m, HP compatible, OEM PN: J4858C JD493A JD118B	82.08%
Sureport- Cisco: SFP 1000Base-SX 550m, I-temp, Cisco Systems compatible, OEM PN: GLC-SX-MM GLC-SX-MMD SFP-GE-S (GLC-SX-MM-RGD)	83.28%
Passport - Universal: 10km Long Haul SFP, Temperature Hardened	81.00%
Passport - Universal: 10km Long Haul SFP	81.82%
Sureport- Cisco: SFP 1000Base-LX 10km, Cisco Systems compatible, OEM PN: SFP-GE-L GLC-LH-SM GLC-LH-SMD (GLC-LX-SM-RGD)	84.42%
Sureport- HP: SFP 1000Base-LX 10km, HP compatible, OEM PN: JD119B J4859C JD494A	84.42%
Sureport- Cisco: SFP 1000Base-LX 10km, I-temp, Cisco Systems compatible, OEM PN: SFP-GE-L GLC-LH-SM GLC-LH-SMD (GLC-LX-SM-RGD)	85.07%
Sureport- Cisco: SFP 10/100/1000-T 100m, multi-rate, Cisco Systems compatible, OEM PN: GLC-T/SFP-GE-T (10/100/1000)	81.00%
Sureport- HP: SFP 10/100/1000-T 100m, multi-rate, HP compatible, OEM PN: 3CSFP93 J8177C	81.00%
Passport - Universal: 10/100/1000Base-T Copper (RJ-45) SFP, 100m	71.53%
Sureport- Cisco: SFP 10/100/1000-T 100m, multi-rate, Cisco Systems compatible, OEM PN: GLC-T, SFP-GE-T (10/100/1000)	81.00%
Sureport- HP: SFP 10/100/1000-T 100m, multi-rate, HP compatible, OEM PN: 3CSFP93, J8177C	83.71%
Passport - Universal: 10/100/1000Base-T Copper SFP, 100m	79.17%
Passport - Universal: Short haul 10GBase-SR SFP+, 850nm 33/82/300m rated, Temperature Hardened	89.57%
Passport - Universal: 2km Extended Range SFP	77.88%
Passport - Universal: 20km SF GigE SFP, 1310nm	92.57%
Passport - Universal: 20km SF GigE SFP, 1490nm	92.57%
Sureport- HP: SFP SF 1000Base-BX 1310 Tx/ 1490 Rx, 20km, HP compatible, OEM PN: JD098B J9143B	92.57%
Sureport- Cisco: SFP SF 1000Base-BX 1310Tx/1490Rx, 20km, Cisco Systems compatible, OEM PN: GLC-BX-U	92.57%
Sureport- HP: SFP SF 1000Base-BX 1490 Tx/ 1310Rx, 20km, HP compatible, OEM PN: JD099B J9142B	92.57%

Appendix C, Pricing Index
Champion Optical Network Engineering LLC dba Champion ONE
DIR-CPO-4418

PRODUCT DESCRIPTION	DIR Customer Discount % off MSRP
Sureport- Cisco: SFP SF 1000Base-BX 1490Tx/1310Rx 20km, Cisco Systems compatible, OEM PN: GLC-BX-D	92.57%
25GBase-SR SFP28, 70m/100m, MMF, LC/UPC connector	81.00%
40km Intermediate Reach SFP Revision 2, Temperature Hardened	88.26%
SFP+ 10GBASE-SR 300m OM3/400m OM4, , Cisco Systems compatible, OEM PN: SFP-10G-SR SFP-10G-SR-X	89.83%
SFP+ 10GBASE-SR 30m, HP compatible, OEM PN: JD092B J9150	89.83%
Short haul 10GBase-SR SFP+, 850nm 33/82/300m rated	89.83%
20km SF GigE SFP, 1310nm, Temperature Hardened	89.42%
20km SF GigE SFP, 1490nm, Temperature Hardened	89.42%
Long haul 10GBase-LR SFP+, 1310nm, 10km rated, Temperature Hardened	69.53%
SFP+ 10GBASE-LR 10km, I-temp, Cisco Systems compatible, OEM PN: SFP- 10G-LR SFP-10G-LR-X	82.76%
40km SF GigE SFP, 1310nm, Temperature Hardened	89.12%
40km SF GigE SFP, 1550nm, Temperature Hardened	89.12%
33m/82m/300m 10GBase-SR/SW, 10G FC XFP, Temperature Hardened	81.00%
40km Intermediate Reach SFP Revision 2	88.72%
SFP 1000Base-EX 40km (1310nm), HP compatible, OEM PN: JD061A	88.72%
SFP 1000Base-EX 40km, Cisco Systems compatible, OEM PN: GLC-EX-SMD	88.72%
Long haul 10GBase-LR SFP+, 1310nm, 10km rated	88.96%
SFP+ 10GBASE-LR 10km, Cisco Systems compatible, OEM PN: SFP-10G-LR SFP- 10G-LR-X	88.96%
SFP+ 10GBASE-LR 10km, HP compatible, OEM PN: JD094B J9151	88.96%
40km Gigabit Ethernet CWDM SFP, 1xx0nm Revision 2, Temperature- Hardened	68.44%
80km Extended Reach SFP, Temperature-Hardened	78.58%
LRM 10GBase-LRM SFP+, 1310nm, 220m rated	81.00%
SFP+ 10GBASE-LRM 220m, Cisco Systems compatible, OEM PN: SFP-10G- LRM	81.00%
SFP+ 10GBASE-LRM 220m, HP compatible, OEM PN: JD093B	81.00%
40km SF GigE SFP, 1310nm	81.00%
40km SF GigE SFP, 1550nm	81.00%
SFP SF 1000Base-BX 1310Tx/1550Rx, 40km, Cisco Systems compatible	89.40%
SFP SF 1000Base-BX 1550Tx/1310Rx, 40km, Cisco Systems compatible	89.40%
80km CWDM SFP, 1xx0nm Revision 2 (PIN receiver), Temperature-Hardened	67.75%

Appendix C, Pricing Index
Champion Optical Network Engineering LLC dba Champion ONE
DIR-CPO-4418

PRODUCT DESCRIPTION	DIR Customer Discount % off MSRP
Single-Rate 25GBase-LR SFP28 10km SMF LC/UPC connector	81.00%
40km Gigabit Ethernet CWDM SFP, 1xx0nm Revision 2	81.00%
SFP 1000BASE-EX CWDM 1xx0nm 40km, multi-rate, Cisco Systems compatible, OEM PN: 0	84.35%
10km 10GBase-LR/LW, 10G FC, OC-192 XFP, Temperature Hardened	81.12%
33m/82m/300m 10GBase-SR/SW, 10G FC XFP	83.92%
80km Extended Reach SFP	83.92%
SFP 1000Base-ZX 80km, Cisco Systems compatible, OEM PN: GLC-ZX-SM SFP-GE-Z (GLC-ZX-SM-RGD)	83.92%
SFP 1000Base-ZX 80km, HP compatible, OEM PN: JD063B 3CSFP97 J4860C	83.92%
XFP 10GBASE-SR 30m, Cisco Systems compatible, OEM PN: XFP-10G-MM-SR	83.92%
XFP 10GBASE-SR 30m, HP® compatible, OEM PN: 3CXFP94	83.92%
100/1000/10GBase-T SFP+, RJ45 connector, 30m rated	60.40%
80km CWDM SFP, 1xx0nm Revision 2 (PIN receiver)	84.38%
SFP 1000BASE-ZX CWDM 1xx0nm 80km, multi-rate, Cisco Systems compatible, OEM PN: CWDM-SFP-1470	89.15%
SFP 1000BASE-ZX CWDM 1xx0nm 80km, multi-rate, HP compatible, OEM PN: J9677x - J9684x JD109A - JD116A	89.15%
Single Fiber XFP 10GE LAN/WAN, 10G FC 10km, 1270nm Tx, Temperature Hardened	81.00%
Single Fiber XFP 10GE LAN/WAN, 10G FC 10km, 1330nm Tx, Temperature Hardened	81.00%
80km SF GigE SFP, 1490nm, Temperature Hardened	81.00%
80km SF GigE SFP, 1590nm, Temperature Hardened	81.00%
SFP SF 1000Base-BX 1490Tx/1590Rx, 80km, Cisco Systems compatible	81.00%
SFP SF 1000Base-BX 1590Tx/1490Rx, 80km, Cisco Systems compatible	81.00%
Single Fiber SFP+ 10GE LAN and WAN, 10km, 1270nm Temperature-Hardened	82.84%
Single Fiber SFP+ 10GE LAN and WAN, 10km, 1330nm Temperature-Hardened	82.84%
SFP SF 1000Base-BX 1550Tx/1490Rxm, 80km, Cisco Systems compatible	81.00%
80km SF GigE SFP, 1490nm	83.84%
80km SF GigE SFP, 1590nm	83.84%
SFP SF 1000Base-BX 1490Tx/1550Rx, 80km, Cisco Systems compatible	81.00%

Appendix C, Pricing Index
Champion Optical Network Engineering LLC dba Champion ONE
DIR-CPO-4418

PRODUCT DESCRIPTION	DIR Customer Discount % off MSRP
40GBase-ESR4 QSFP+, 300m, MMF 1x12 MPO connector	81.00%
Single-Rate 25GBase-LR SFP28 10km SMF LC/UPC connector temp-hardened	81.00%
160km CWDM SFP, 1xx0nm, very long haul	53.40%
10km 10GBase-LR/LW, 10G FC, OC-192 XFP	85.95%
XFP 10GBASE-LR 10km, multi-rate, Cisco Systems compatible, OEM PN: XFP10GLR-192SR-L XFP10GLR192SR-RGD XFP-10GLR-OC192SR	85.95%
XFP 10GBASE-LR 10km, multi-rate, HP® compatible, OEM PN: JD108B	85.95%
40GBase-SR4 QSFP+, 100m/150m, MMF 1x12 MPO connector	83.15%
QSFP+ 40GBase-SR4 850nm, 100/150m, Cisco Systems compatible, OEM PN: QSFP-40G-SR4	83.15%
SFP+ SF 10GBase-LR 1270 Tx/1330 Rx 10km, Cisco Systems compatible	85.27%
SFP+ SF 10GBase-LR 1270 Tx/1330 Rx 10km, HP compatible	85.27%
SFP+ SF 10GBase-LR 1330 Tx/ 1270 Rx 10km, Cisco Systems compatible	85.27%
SFP+ SF 10GBase-LR 1330 Tx/ 1270 Rx 10km, HP compatible	85.27%
Single Fiber SFP+ 10GE LAN and WAN, 10km, 1270nm	86.74%
Single Fiber SFP+ 10GE LAN and WAN, 10km, 1330nm	86.74%
Single Fiber XFP 10GE LAN/WAN, 10G FC 10km, 1270nm Tx	83.18%
Single Fiber XFP 10GE LAN/WAN, 10G FC 10km, 1330nm Tx	83.18%
XFP SF 10GBase-LR 1270nm Tx, 10km, Cisco Systems compatible	81.00%
XFP SF 10GBase-LR 1330nm Tx, 10km, Cisco Systems compatible	81.00%
160km Extended Long Reach SFP, Temperature-Hardened	81.00%
Single Fiber XFP 10GE LAN/WAN, 10G FC 40km, 1270nm Tx, Temperature Hardened	81.00%
Single Fiber XFP 10GE LAN/WAN, 10G FC 40km, 1330nm Tx, Temperature Hardened	81.00%
120km CWDM SFP, 1xx0nm, 1470-1610nm Revision 2	87.38%
Extended-reach 10GBase-ER SFP+, 1550nm, 40km rated, Temperature Hardened	81.00%
120km SF GigE SFP, 1490nm	81.00%
120km SF GigE SFP, 1590nm	81.00%
120km SF GigE SFP, 1490nm, Temperature Hardened	78.65%
120km SF GigE SFP, 1590nm, Temperature Hardened	78.65%
Single Fiber SFP+ 10GE LAN and WAN, 40km, 1270nm Temperature- Hardened	83.83%
Single Fiber SFP+ 10GE LAN and WAN, 40km, 1330nm Temperature- Hardened	83.83%
120km Extended Long Reach SFP	81.78%

Appendix C, Pricing Index
Champion Optical Network Engineering LLC dba Champion ONE
DIR-CPO-4418

PRODUCT DESCRIPTION	DIR Customer Discount % off MSRP
80km 10G CWDM SFP+ 1xx0nm Temperature Hardened	37.96%
160km Extended Long Reach SFP	87.05%
Single-Rate 100GBase-LR4 QSFP28 10km SMF LC/UPC connector 4.0W power consumption	32.31%
Multi-rate DWDM SFP channel xx (ITU ch.), 120km rated Rev. 2, Temperature Hardened	62.58%
40GBase-IR4 QSFP+, 2km SMF LC connector	81.00%
40GBase-PSM LR4 QSFP+, 10km SMF MPO 8° angled connector	81.00%
Single Fiber SFP+ 10GE LAN and WAN, 60km, 1270nm Temperature-Hardened	81.00%
Single Fiber SFP+ 10GE LAN and WAN, 60km, 1330nm Temperature-Hardened	81.00%
SFP+ SF 10GBase-ER 1270 Tx/1330 Rx 40km, Cisco Systems compatible	81.35%
SFP+ SF 10GBase-ER 1270 Tx/1330 Rx 40km, HP compatible	81.35%
SFP+ SF 10GBase-ER 1330 Tx/ 1270 Rx 40km, Cisco Systems compatible	81.35%
SFP+ SF 10GBase-ER 1330 Tx/ 1270 Rx 40km, HP compatible	81.35%
Single Fiber SFP+ 10GE LAN and WAN, 40km, 1270nm	81.35%
Single Fiber SFP+ 10GE LAN and WAN, 40km, 1330nm	81.35%
Extended-reach 10GBase-ER SFP+, 1550nm, 40km rated	84.41%
Multi-rate DWDM SFP channel xx (ITU ch.), 80km rated Rev. 2	84.41%
Multi-rate DWDM SFP channel xx (ITU ch.), 80km rated Rev. 2, Temperature Hardened	69.71%
SFP 1000BASE-ZX DWDM CHxx 80km, multi-rate, Cisco Systems compatible, OEM PN: DWDM-SFP-2121	81.00%
SFP 1000BASE-ZX DWDM CHxx 80km, multi-rate, HP compatible	81.00%
SFP+ 10GBASE-ER 40km, Cisco Systems compatible, OEM PN: SFP-10G-ER	81.00%
SFP+ 10GBASE-ER 40km, HP compatible, OEM PN: JG234A J9153	81.00%
Multi-rate DWDM SFP channel xx (ITU ch.), 120km rated Rev. 2	72.73%
SFP 1000BASE-ZX DWDM CHxx 120km, multi-rate, Cisco Systems compatible, OEM PN: DWDM-SFP-2121	81.00%
40km 10GBase-ER/EW, 10G FC, OC-192 XFP Temperature Hardened	81.00%
40GBase-PSM IR4 QSFP+, 1.4km SMF MPO 8° angled connector	81.00%
SFP+ SF 10GBase-ER 1270 Tx/1330 Rx 60km, Cisco Systems compatible	81.00%
SFP+ SF 10GBase-ER 1270 Tx/1330 Rx 60km, HP compatible	81.00%
SFP+ SF 10GBase-ER 1330 Tx/ 1270 Rx 60km, Cisco Systems compatible	81.00%
SFP+ SF 10GBase-ER 1330 Tx/ 1270 Rx 60km, HP compatible	81.00%

Appendix C, Pricing Index
Champion Optical Network Engineering LLC dba Champion ONE
DIR-CPO-4418

PRODUCT DESCRIPTION	DIR Customer Discount % off MSRP
Single Fiber SFP+ 10GE LAN and WAN, 60km, 1270nm	81.00%
Single Fiber SFP+ 10GE LAN and WAN, 60km, 1330nm	81.00%
Single Fiber XFP 10GE LAN/WAN, 10G FC 40km, 1270nm Tx	83.66%
Single Fiber XFP 10GE LAN/WAN, 10G FC 40km, 1330nm Tx	83.66%
XFP SF 10GBase-ER 1270nm Tx, 40km, Cisco Systems compatible	83.66%
XFP SF 10GBase-ER 1330nm Tx, 40km, Cisco Systems compatible	83.66%
Single Fiber XFP 10GE LAN/WAN, 10G FC 60km, 1270nm Tx	81.00%
Single Fiber XFP 10GE LAN/WAN, 10G FC 60km, 1330nm Tx	81.00%
XFP SF 10GBase-ER 1270nm Tx, 60km, Cisco Systems compatible	81.00%
XFP SF 10GBase-ER 1330nm Tx, 60km, Cisco Systems compatible	81.00%
100GBase-SR4 QSFP28, 70m/100m,MMF MPO connector	71.04%
Single-Rate 100GBase-CWDM4 QSFP28 10km SMF LC/UPC connector	73.21%
100GBase-PSM IR4 QSFP28, 2km SMF MPO 8° angled connector	71.52%
40km Multi-protocol 10G CWDM XFP 1xx0nm, Temperature Hardened	81.00%
40km 10GBase-ER/EW, 10G FC, OC-192 XFP	81.00%
XFP 10GBASE-ER 40km, multi-rate, Cisco Systems compatible, OEM PN: XFP-10GER-192IR+ XFP10GER-192IR-L XFP10GER192IR-RGD XFP-10GER-OC192IR	81.00%
XFP 10GBASE-ER 40km, multi-rate, HP® compatible, OEM PN: 3CXFP96	81.00%
40km 10G CWDM SFP+ 1xx0nm Temperature Hardened	81.00%
40km Multi-protocol 10G CWDM XFP 1xx0nm	81.00%
70km Multi-protocol 10G CWDM XFP 1xx0nm, Temperature Hardened	81.00%
Multi-rate DWDM SFP+, ITU channel xx, 80km rated, Temperature Hardened	67.98%
Multi-rate DWDM SFP+, ITU channel xx, 40km rated, Temperature Hardened	81.00%
Multi-rate DWDM SFP+, ITU channel xx, 40km rated	81.00%
SFP+ 10GBASE-ER DWDM CHxx 40km, Cisco Systems compatible	81.00%
SFP+ 10GBASE-ER DWDM CHxx 40km, HP compatible	81.00%
40GBase-LR4 QSFP+, 10km, SMF LC connector	82.87%
QSFP+ 40GBase-LR4 10 km, Cisco Systems compatible, OEM PN: QSFP-40G-LR4	82.87%
40km 10G CWDM SFP+ 1xx0nm	81.00%
SFP+ 10GBASE-ER CWDM 1xx0nm 40km, HP compatible	81.00%
SFP+ 10GBASE-ZR CWDM 1xx0nm, 40km, Cisco Systems compatible	81.00%
40GBase-ER4 QSFP+, 40km, SMF LC connector	81.00%
Long Reach 10GBase-ZR SFP+, 1550nm, 80km rated, Temperature Hardened	81.00%

Appendix C, Pricing Index
Champion Optical Network Engineering LLC dba Champion ONE
DIR-CPO-4418

PRODUCT DESCRIPTION	DIR Customer Discount % off MSRP
Multi-rate tunable DWDM XFP tunable to channels 17-61, 50Ghz spacing, amplifiable, 80km-rated.	81.00%
Multi-rate tunable (via uTune Director) DWDM XFP channel xx.x (ITU ch.), 80km rated. Amplifiable, 50GHz spacing.	81.00%
QSFP+ 40GBase-ER4, 40km, SMF LC connector, OEM PN: QSFP-40G-ER4	81.00%
Multi-protocol tunable SFP+, 80km rated, with limiting electrical interface	74.37%
10G multi-rate DWDM XFP channel xx, 40km rated	81.00%
10G multi-rate DWDM XFP channel xx, 80km rated, temperature-hardened	81.00%
XFP SF 10GBase-ZR 1490nm Tx, 80km, Cisco Systems compatible	81.00%
XFP SF 10GBase-ZR 1550nm Tx, 80km, Cisco Systems compatible	81.00%
Single Fiber XFP 10GE LAN/WAN, 10G FC 80km, 1490nm Tx	81.00%
Single Fiber XFP 10GE LAN/WAN, 10G FC 80km, 1550nm Tx	81.00%
80km 10GBase-ZR/ZW, 10G FC, OC-192 XFP Rev 2 Temperature Hardened	84.51%
Long Reach 10GBase-ZR SFP+, 1550nm, 100km rated	74.15%
SFP+ SF 10GBase-ZR 1490 Tx/1550 Rx 80km, Cisco Systems compatible	81.00%
SFP+ SF 10GBase-ZR 1550 Tx/ 1490 Rx 80km, Cisco Systems compatible	81.00%
Single Fiber SFP+ 10GE LAN and WAN, 80km, 1490nm	81.00%
Single Fiber SFP+ 10GE LAN and WAN, 80km, 1550nm	81.00%
70km Multi-protocol 10G CWDM XFP 1xx0nm	82.08%
Single-Rate 100GBase-LR4 Lite QSFP28 2km SMF LC/UPC connector	64.87%
XFP 10GBASE-ZR CWDM 1xx0nm 80km, multi-rate, Cisco Systems compatible, OEM PN: CWDM-XFP-4747	81.00%
80km 10GBase-ZR/ZW, 10G FC, OC-192 XFP Rev 2	81.00%
XFP 10GBASE-ZR 80km, multi-rate, Cisco Systems compatible, OEM PN: XFP-10GZR-OC192LR	81.00%
Single-Rate 100GBase-CWDM4 QSFP28 2km SMF LC/UPC connector	88.02%
40GBase-LM4 QSFP+ 140m/160m, MMF LC connector	81.00%
10G multi-rate DWDM XFP channel xx, 80km rated	81.00%
Long Reach 10GBase-ZR SFP+, 1550nm, 80km rated	81.00%
SFP+ 10GBASE-ZR 80km, Cisco Systems compatible, OEM PN: SFP-10G-ZR	81.00%
SFP+ 10GBASE-ZR 80km, HP compatible	81.00%
XFP 10GBASE-DWDM CHxx 80km, multi-rate, Cisco compatible, OEM PN: XFP-DWDM	81.00%
Multi-rate DWDM SFP+, ITU channel xx, 80km rated	82.86%

Appendix C, Pricing Index
Champion Optical Network Engineering LLC dba Champion ONE
DIR-CPO-4418

PRODUCT DESCRIPTION	DIR Customer Discount % off MSRP
SFP+ 10GBASE-ZR DWDM CHxx 80km, Cisco Systems compatible, OEM PN: DWDM-SFP10G-wx.yz	81.00%
SFP+ 10GBASE-ZR DWDM CHxx 80km, HP compatible	81.00%
80km 10G CWDM SFP+ 1xx0nm	81.00%
SFP+ 10GBASE-ZR CWDM 1xx0nm, 70km, Cisco Systems compatible	81.30%
SFP+ 10GBASE-ZR CWDM 1xx0nm, 70km, HP compatible	81.30%
100-120km 10GBase-ZR/ZW, OC-192 Ext. Range XFP	81.00%
100GBase-SR10/10x11.2 Gb/s MM OTN CFP2, 100/150m, MMF MPO connector	81.00%
100GBase-SR4 CFP4, 70m/100m, MMF MPO connector	81.00%
100GBase-SR10 CFP, 100/150m, MMF MPO connector	81.00%
Single-Rate 100GBase-CLR4 QSFP28 2km SMF LC/UPC connector	84.16%
Single-Rate 100GBase-LR4 QSFP28 10km SMF LC/UPC connector 4.5W power consumption	80.86%
100GBase-SR4/4x28 Gb/s MM OTN CFP4, 70/100m, MMF MPO connector	81.00%
100GBase-SR10 CFP2, 82m/300m, MMF MPO connector	81.00%
100GBase-SR10/10x11.2 Gb/s MM OTN CFP, 100/150m, MMF MPO connector	81.00%
Single-Rate 100GBase-ER4 Lite QSFP28 40km (w/FEC) / 30km (w/o FEC), SMF LC connector, C-Temp	68.09%
Single-Rate 100GBase-LR4 CFP 10km SMF LC/UPC connector, Gen 2	81.00%
Single-Rate 100GBase-LR4 CFP2 10km SMF LC/UPC connector	81.00%
Single-Rate 100GBase-LR4 CFP4 10km SMF LC/UPC connector	81.00%
Single-Rate 100GBASE-4WDM40 QSFP28 40km (w/FEC), SMF LC connector, C-Temp	70.77%
Multi-Rate 100GBase-LR4/OTU4 CFP 10km SMF LC/UPC connector, Gen 2	81.00%
Multi-Rate 100GBase-LR4/OTU4 CFP4 10km SMF LC/UPC connector	81.00%
Multi-Rate 100GBase-LR4/OTU4 CFP2 10km SMF LC/UPC connector	92.95%
Single-Rate 100GBase-ER4 CFP2 40km SMF, LC/UPC connector	85.67%
1310/CWDM overlay 8+1 channel, 1470-1610nm, Single wide LGX with 2% MON, LC	75.57%
CWDM 8 channel, 1470-1610nm, Single wide LGX with 2% MON, LC	87.30%
DWDM 100GHz 16CH, Ch 20 start, no skips, with 2% Mon, 1310PB, 1RU LC	65.05%
DWDM, 100GHz 16CH, Ch 21 start, no skips, with 2% Mon, 1310PB, 1RU LC	62.36%
DWDM, 100GHz 40CH, Ch 20 start, no skips, with 2% Mon, 1310PB, 1RU LC	69.76%

Appendix C, Pricing Index
Champion Optical Network Engineering LLC dba Champion ONE
DIR-CPO-4418

PRODUCT DESCRIPTION	DIR Customer Discount % off MSRP
DWDM, 100GHz 40CH, Ch 21 start, no skips, with 2% Mon, 1310PB, 1RU LC	73.12%
DWDM, 100GHz, 8CH, C16-C23, 8-skip-1 with 2% MON and EXP port, LGX, LC	62.00%
DWDM, 100GHz, 8CH, C25-C32, 8-skip-1 with 2% MON and EXP port, LGX, LC	62.00%
DWDM, 100GHz, 8CH, C43-C50, 8-skip-1 with 2% MON and EXP port, LGX, LC	62.00%
DWDM, 100GHz, 8CH, C52-C59, 8-skip-1 with 2% MON and EXP port, LGX, LC	62.00%
DWDM, 100GHz, 8CH, C34-C41, 8-skip-1 with 2% MON and EXP port, LGX, LC	62.00%