

SUREPORT DATA SHEET

Cisco-Compatible Dual Fiber XFP



Champion ONE's Dual Fiber XFP product line supports a variety of protocols over a wide range of distance and temperature options. These optics are fully MSA-compliant and offer direct compatibility with your existing switches and routers.

Champion ONE Sureport transceivers are programmed for one-to-one compatibility with your existing OEM platforms.

Technical Specifications

STANDARDS AND REGULATORY COMPLIANCE

RoHS compliant
XFP MSA (multi-source agreement)

PROTOCOLS AND DATA RATES

Product line supports the following protocols and data rates:
10G Ethernet LAN/WAN
10G Fibre Channel
SONET OC-192
UL/CSA Class 3862.07 / 3862.87

DIMENSIONS

71 x 18.5 x 8.5 mm ; 300 g

CONNECTOR

Duplex LC connector

WARRANTY

All feature a limited 5-year warranty

C1 Part Number	Transmit Wavelength (nm)	Fiber Type	Rated Distance (km)	Temp Range (°C)	Description	Tx (min/max) (dBm)	Rx (min/max) (dBm)	Substitute for Cisco® part #
10G MULTI-PROTOCOL								
10GEXFP-SR-CSC	850	MMF	0.03	0 to 70	XFP 10GBASE-SR 30m, Cisco Systems compatible	-7.3 / -1.2	-9.9 / -1.0	XFP-10G-MM-SR
10GEXFP-LR(I)-CSC	1310	SMF	10	0 to 70 (-40 to 85)	XFP 10GBASE-LR 10km, multi-rate, Cisco Systems compatible	-6.0 / -1.0	-15.0 / 0.5	XFP10GLR-192SR-L XFP10GLR192SR-RGD XFP-10GLR-OC192SR
10GEXFP-ER(I)-CSC	1550	SMF	40	0 to 70 (-40 to 85)	XFP 10GBASE-ER 40km, multi-rate, Cisco Systems compatible	-1.0 / 4.0	-16.5 / -1.0	XFP-10GER-192IR+ XFP10GER-192IR-L XFP10GER192IR-RGD XFP-10GER-OC192IR
10GEXFP-ZR-CSC	1550	SMF	80	0 to 70	XFP 10GBASE-ZR 80km, multi-rate, Cisco Systems compatible	0.0 / 4.0	-24.0 / -7.0	XFP-10GZR-OC192LR

* Parts are intended as one-to-one replacements. Please verify that the OEM part number is compatible with your system before ordering. If you have questions regarding specific switches and routers, please contact your Champion ONE sales representative for support. In most cases, a customized solution can be developed to meet your needs.